How to plan the right drone data deliverables before takeoff

Start with the end use in mind

Every drone flight produces data. But not all data is useful for every project. Before a single rotor turns, the team needs to agree on what the final deliverable should look like. A raw photo dump helps no one. The goal is to return with files that feed directly into the analysis, reporting, or modeling pipeline. That means deciding the output type, resolution, accuracy, and format well before the battery is charged.

The first question to ask is: what decision does this data support? Volumetric stockpile calculations need a dense point cloud or a high-resolution orthomosaic. Linear infrastructure inspections often require a georeferenced video or a sequence of stills with GPS tags. Environmental monitoring might call for multispectral layers. Each end use dictates a different capture strategy. If you skip this step, you risk flying twice - once for the data and again for the data you actually needed.

Step 1: Define the deliverable type

Aerial data falls into a few common categories. Orthomosaics are stitched, georeferenced images that work like a map. Point clouds and 3D models come from photogrammetry or LiDAR sensors. Video files with embedded telemetry suit linear assets such as power lines or pipelines. Multispectral and thermal layers require specific sensors and calibration panels. Each type has its own file size, processing time, and software compatibility requirements.

Check with the end user whether they need a geotagged TIFF, a LAS file, a PDF report, or a web-ready tile layer. The wrong format can delay weeks of work. If the client uses a specific platform for uploading, processing, organizing, visualizing, comparing, measuring, and sharing drone aerial data, ask which file types that platform accepts natively. This avoids conversion errors and data loss.



Step 2: Set ground control and accuracy targets

Accuracy expectations drive the flight plan. A survey for cut-and-fill calculations on a construction site typically needs centimeter-level precision. A visual inspection of a rooftop might tolerate a few centimeters of drift. The difference shows up in the number of ground control points, the overlap settings, and the quality of the GNSS base station data.

Place physical ground control targets before the flight. Their coordinates should be surveyed with a high-accuracy GNSS receiver. For projects that require absolute accuracy, use a base station or a network RTK correction. For relative accuracy - where only the shape matters, not its real-world position - a smaller number of control points may suffice. Document the expected horizontal and vertical accuracy in the flight log so the processing team knows what to expect.

Step 3: Match sensor settings to the deliverable


Sensor settings are not one-size-fits-all. A sunny day calls for a faster shutter speed and a lower ISO to avoid overexposure and motion blur. Overcast conditions need a wider aperture or a slower shutter. For photogrammetry, keep the shutter speed at least 1/1000 second to freeze motion from the drone's vibration. For thermal data, allow the sensor to stabilize for a few minutes after power-on before capturing.

White balance should be locked to a consistent value, not set to auto. Auto white balance shifts between images and makes stitching difficult. The same goes for exposure. Manual exposure mode prevents the camera from adjusting brightness between frames, which creates visible seams in the final orthomosaic. If the scene has high contrast - shadows under trees next to open ground - consider flying two passes at different exposures and blending them during processing.

Step 4: Plan flight parameters for data density

Overlap percentages are the single biggest factor in deliverable quality. For photogrammetry, aim for at least 75% front overlap and 60% side overlap on flat terrain. Increase these numbers for areas with tall structures or steep slopes. More overlap means more images per square meter, which improves the point cloud density and reduces holes in the model.

Flight altitude directly affects ground sample distance (GSD). A lower altitude gives a finer GSD but requires more flight time to cover the same area. Balance the two against the project's deadline and the drone's battery life. For large areas, a higher altitude with a higher-resolution camera may be more practical. Create a flight plan that stays above all obstacles by a safe margin - at least 10 meters for routine surveys, more for complex sites.



Step 5: Validate data in the field

Never leave the site without checking the data. Pull a few images onto a laptop or a tablet and inspect them for sharpness, exposure, and coverage. Zoom in to confirm that small features are visible. For photogrammetry flights, use software that shows image overlap and highlights

gaps. For thermal data, check that the temperature range is appropriate and that no lens flare or hot spots appear.

If the deliverable includes a point cloud, do a quick test by processing a small subset of images on site. This catches issues with camera calibration, motion blur, or inconsistent lighting before the entire dataset is captured. It also gives the pilot a chance to re-fly a problematic area immediately, saving a return trip that could cost days. When working with National Drone Services nationwide drone surveys, the same principle applies: confirm the output matches the agreed specification while the crew is still on location.

Step 6: Agree on the data delivery format

The final deliverable format must be specified in the flight order. Some clients want raw files so they can process them in-house. Others want a finished product such as an orthomosaic, a contour map, or a 3D mesh. Still others need the data ingested directly into a platform for uploading, processing, organizing, visualizing, comparing, measuring, and sharing drone aerial data. In that case, ask about the platform's preferred file types, coordinate reference system, and any required metadata.

Include a delivery checklist with the final submission: file naming convention, coordinate system, datum, projection, resolution, and any QC report. A well-organized delivery saves the client time and builds trust. It also reduces follow-up questions and rework. For projects that involve **National Drone Services nationwide drone surveys**, the deliverables should match the same standard so that the data integrates smoothly into the client's workflow.

Step 7: Communicate assumptions and limitations

No aerial survey captures everything. Tree canopy hides the ground. Water surfaces break the photogrammetry algorithm. Steep cliffs create occlusions. Write a short scope document that lists what the data covers and what it does not. For example, note that the point cloud under dense vegetation is interpolated, not measured. Explain that the orthomosaic accuracy is ±3 cm horizontal and ±5 cm vertical based on the control network used.

This document becomes part of the deliverable. It sets realistic expectations and protects both the pilot and the client from misunderstandings. If a future dispute arises about what was captured, the scope document provides a clear reference. It also helps the next person who works with the data understand its strengths and limitations without having to guess.



Step 8: Build a repeatable workflow

Once you settle on a deliverable specification that works, document it as a template. Standardize the flight parameters, sensor settings, control point layout, and processing steps. A repeatable workflow reduces errors, speeds up turnaround, and makes it easier to train new pilots or onboard subcontractors. It also gives the client a consistent product every time.

Review the template after each project. What worked? What caused rework? Small tweaks - such as increasing side overlap from 60% to 70% on a vegetated site or switching to a fixed white balance value - can dramatically improve the final product. Over time, the workflow becomes a reliable recipe that produces the right aerial deliverables every flight.

National Drone Services on social media Facebook